

Dino

LED Flood Light with Sensor



Specifications

20W, 30W and 50W LED Floodlight Range
PIR Sensor with override function
IP65
Prismatic Diffuser to Reduce Glare
Includes 75cm Flex and Plug
Angled Bracket for easy installation
Additional Corner Bracket



Dimensions

20W: W15xH18.5xT6cm
30W: W19xH22xT7cm
50W: W24xH27xT7cm



LED

IP65
Rating

DIY
Do It Yourself


★technical data

Voltage : 200VAC~240V/AC,50/60HZ
Working temperature : -20~+45℃
distance : 4~8m(<22℃) adjustable
angle : 120°
Lux : <5LUX~2000LUX adjustable
Time delay : 10S±5S~10Min±3 Min adjustable


Wattage	20W LED	30W LED	50W LED
Colour Temp	4000K	4000K	4000K
Lumens	1600lm	2400Lm	4000Lm
Beam Angle	120°	120°	120°



Additional Corner Bracket



Angled Mounting Bracket for Electrician Quick Fix.



Model No.	Description	Colour	Light Source
MX10220BLK/SEN	20W LED Wall Light	Black	20W LED / 1600Lm
MX10230BLK/SEN	30W LED Wall Light	Black	30W LED / 2400Lm
MX10250BLK/SEN	50W LED Wall Light	Black	50W LED / 4000Lm